



# CAE Modular Acoustic Enclosure

24 – 220 kVA Range

The intelligent and striking design of the 24 – 220 kVA enclosure range meets the demands of diverse applications. Extremely durable, the enclosures are designed to resist corrosion and handling damage.

All FG Wilson weatherproof sound attenuated enclosures are the result of continuing research and development by our specialist acoustic engineers. **These enclosures reduce sound levels to comply with the stage 2 levels of the European Community Directive 2000/14/EC which became effective 3 January 2006.**

## Durable and Robust Construction

- Manufactured from galvanised steel
- Advanced powder coating paint finish
- Single piece main roof
- Baseframe extends beyond enclosure protecting against handling damage
- Minimal external fixings exposed to environment
- Zinc plated fasteners
- Corner posts and air handling units manufactured from high grade composite material

## Excellent Service and Maintenance Access

- Side hinged doors on both sides of the enclosure incorporating lift-off hinges at 45 degrees
- Radiator fill via removable, flush mounted rain cap fitted with compression seal
- Lube oil drain valves / Coolant drain valves
- Removable end panels allow access to radiator, exhaust outlet and alternator rear
- Doors positioned for optimum access to frequently serviced items

## Security and Safety

- Secure, lockable doors prevent unauthorised access to control panel, fuel fill and battery
- Emergency stop button mounted on exterior, convenient to control panel
- Cooling fan and battery charging alternator fully guarded

## Transportability

- Optional tested and certified lifting arch
- Lifting and drag points on baseframe facilitating handling from both sides

Head Office

St Ivel Way, Warmley, Bristol BS30 8TY  
T. 0370 850 0858 F. 0370 850 0851

[www.powerelectrics.com](http://www.powerelectrics.com)  
[enquiries@powerelectrics.com](mailto:enquiries@powerelectrics.com)



AUTHORISED DEALER



## Sound Attenuated (SA) Sound Pressure Levels (dBA)

Generator Set Model		50 Hz							60 Hz					
		LWA	15m (50ft)		7m (23ft)		1m (3ft)		15m (50ft)		7m (23ft)		1m (3ft)	
			75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load
<b>3 Phase Models</b>														
P33-3	Prime	93	60.5	61.8	66.5	67.8	76.3	78.4	60.6	62.7	66.6	68.7	77.6	79.9
	Standby	93	60.9	62.4	66.9	68.4	76.9	79.4	61.2	63.8	67.2	69.8	78.2	81.1
P33-6	Prime	94	59.4	61.3	65.4	67.3	76.5	78.6	-	-	-	-	-	-
	Standby	94	60.0	62.1	66.0	68.1	77.1	79.6	-	-	-	-	-	-
P50-3	Prime	93	56.7	57.7	62.7	63.7	76.7	77.9	59.7	60.8	65.7	66.8	79.5	80.8
	Standby	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
P50-4	Prime	90	55.7	56.4	61.7	62.4	75.3	75.5	-	-	-	-	-	-
	Standby	90	55.9	56.7	61.9	62.7	75.4	75.6	-	-	-	-	-	-
P55-3	Prime	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
	Standby	93	57.3	58.9	63.3	64.9	77.4	79.2	60.5	62.2	66.5	68.2	80.5	82.4
P55-4	Prime	91	56.2	56.5	62.2	62.5	75.3	75.5	-	-	-	-	-	-
	Standby	91	56.3	56.7	62.3	62.7	75.3	75.6	-	-	-	-	-	-
P65-5	Prime	93	57.6	59.4	63.6	65.4	77.8	79.7	61.0	63.0	67.0	69.0	81.0	83.3
	Standby	93	58.1	60.5	64.1	66.5	78.3	80.8	61.5	63.8	67.5	69.8	81.6	84.2
P65-6	Prime	91	57.7	58.5	63.7	64.5	75.8	77.1	-	-	-	-	-	-
	Standby	91	57.9	58.9	63.9	64.9	76.2	77.8	-	-	-	-	-	-
P88-3	Prime	92	57.7	59.1	63.7	65.1	76.0	77.0	60.6	61.2	66.6	67.2	79.0	79.5
	Standby	92	58.1	59.8	64.1	65.8	76.2	77.4	60.8	61.5	66.8	67.5	79.2	79.6
P88-6	Prime	96	61.3	61.4	67.3	67.4	80.1	80.2	-	-	-	-	-	-
	Standby	96	61.3	61.5	67.3	67.5	80.2	80.3	-	-	-	-	-	-
P110-3	Prime	96	62.4	63.1	68.4	69.1	80.4	81.0	65.2	65.4	71.2	71.4	84.4	84.6
	Standby	96	62.6	63.5	68.6	69.5	80.6	81.3	65.2	65.5	71.2	71.5	84.5	84.7
P110-6	Prime	94	61.4	61.6	67.4	67.6	80.2	80.3	-	-	-	-	-	-
	Standby	94	61.5	61.7	67.5	67.7	80.2	80.4	-	-	-	-	-	-
P150-4	Prime		58.5	58.9	64.5	64.9	77.0	77.3	-	-	-	-	-	-
	Standby		58.6	59.1	64.6	65.1	77.1	77.5	-	-	-	-	-	-
P165-4	Prime		58.6	59.1	64.6	65.1	77.1	77.5	-	-	-	-	-	-
	Standby		58.8	59.4	64.8	65.4	77.2	77.7	-	-	-	-	-	-
P165-5	Prime		58.5	58.9	64.5	64.9	78.0	78.2	-	-	-	-	-	-
	Standby		58.6	59.1	64.6	65.1	78.1	78.3	-	-	-	-	-	-
P200-3	Prime	97	62.0	62.4	68.0	68.4	80.2	80.4	64.9	65.2	70.9	71.2	84.2	84.3
	Standby	97	62.1	62.7	68.1	68.7	80.2	80.5	65	65.3	71	71.3	84.3	84.4
P200-4	Prime	95	59.4	60.2	65.4	66.2	77.7	78.1	63.2	63.6	69.2	69.6	82.9	83.1
	Standby	95	59.6	60.5	65.6	66.5	77.8	78.3	63.3	63.8	69.3	69.8	83.0	83.2
P220-3	Prime	97	62.3	63.5	68.3	69.5	80.0	80.7	-	-	-	-	-	-
	Standby	97	62.7	64.0	68.7	70.0	80.2	81.1	-	-	-	-	-	-


Levels in accordance with European Noise Directive (2000/14/EC).

## Sound Attenuated (SA) Sound Pressure Levels (dBA)

		50 Hz						60 Hz						
		15m (50ft)		7m (23ft)		1m (3ft)		15m (50ft)		7m (23ft)		1m (3ft)		
Generator Set Model		75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	75% Load	100% Load	
<b>Single Phase Models</b>														
P26-3S	Prime	93	60.5	61.8	66.5	67.8	76.3	78.4	-	-	-	-	-	-
	Standby	93	60.9	62.4	66.9	68.4	76.9	79.4	-	-	-	-	-	-
P26-6S	Prime	94	60.5	61.8	66.5	67.8	76.3	78.4	-	-	-	-	-	-
	Standby	94	60.9	62.4	66.9	68.4	76.9	79.4	-	-	-	-	-	-
P40-3S	Prime	93	56.7	57.7	62.7	63.7	76.7	77.9	59.7	60.8	65.7	66.8	79.5	80.8
	Standby	93	56.9	58.2	62.9	64.2	77.0	78.5	60.1	61.5	66.1	67.5	80.0	81.6
P40-4S	Prime	90	55.7	56.4	61.7	62.4	75.3	75.5	-	-	-	-	-	-
	Standby	90	55.9	56.7	61.9	62.7	75.4	75.6	-	-	-	-	-	-
P50-5S	Prime	-	58.1	59.1	64.1	65.1	76.6	77.3	61.1	62.1	67.1	68.1	78.9	80.0
	Standby	-	58.5	59.5	64.5	65.5	76.9	77.6	61.4	62.5	67.4	68.5	79.3	80.5
P55-6S	Prime	-	57.7	58.5	63.7	64.5	75.8	77.1	-	-	-	-	-	-
	Standby	-	57.9	58.9	63.9	64.9	76.2	77.8	-	-	-	-	-	-
P90-3S	Prime	-	62.2	62.8	68.2	68.8	80.2	80.8	65.1	65.3	71.1	71.3	84.4	84.6
	Standby	-	62.4	63.1	68.4	69.1	80.4	81.0	65.2	65.4	71.2	71.4	84.4	84.6
P90-6S	Prime	-	61.3	61.5	67.3	67.5	80.2	80.3	-	-	-	-	-	-
	Standby	-	61.4	61.6	67.4	67.6	80.2	80.3	-	-	-	-	-	-

Levels in accordance with European Noise Directive (2000/14/EC).

## Dimensions, Weights and Fuel Capacities



Generator Set Model	A: mm (in)	B: mm (in)	C: mm (in)	D*: mm (in)	Weight: kg (lb)	Fuel Capacity l (US gal)
<b>3 Phase Models</b>						
P33-3	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P33-6	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P50-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1191 (2626)	219 (58.0)
P50-4	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1183 (2608)	219 (58.0)
P55-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1196 (2637)	219 (58.0)
P55-4	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1236 (2725)	219 (58.0)
P65-5	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1207 (2661)	219 (58.0)
P65-6	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1247 (2749)	219 (58.0)
P88-3	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1391 (3067)	219 (58.0)
P88-6	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1529 (3371)	250 (66.0)
P110-3	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1547 (3411)	250 (66.0)
P110-6	2770 (109.1)	1120 (44.1)	1525 (60.0)	896 (35.3)	1637 (3609)	250 (66.0)
P150-4	3520 (138.6)	1120 (44.1)	1815 (71.5)	1145 (45.1)	1968 (4339)	349 (92.2)
P165-4	3520 (138.6)	1120 (44.1)	1815 (71.5)	1145 (45.1)	2003 (4416)	349 (92.2)
P165-5	3520 (138.6)	1120 (44.1)	1815 (71.5)	1145 (45.1)	2016 (4445)	349 (92.2)
P200-3	3520 (138.6)	1320 (52.0)	1815 (71.5)	1080 (42.5)	2198 (4846)	418 (110.4)
P200-4	3520 (138.6)	1320 (52.0)	1815 (71.5)	1080 (42.5)	2198 (4846)	418 (110.4)
P220-3	3520 (138.6)	1320 (52.0)	1815 (71.5)	1080 (42.5)	2238 (4934)	418 (110.4)
<b>Single Phase Models</b>						
P26-3S	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P26-6S	2120 (83.5)	970 (38.2)	1525 (60.0)	718 (28.3)	991 (2185)	161 (43.0)
P40-3S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1247 (2749)	219 (58.0)
P40-4S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1199 (2643)	219 (58.0)
P50-5S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1340 (2954)	219 (57.0)
P55-6S	2300 (90.6)	1120 (44.1)	1525 (60.0)	795 (31.3)	1355 (2987)	219 (58.0)
P90-3S	2770 (109.1)	1120 (44.1)	1525 (60.0)	899 (35.4)	1613 (3556)	250 (66.0)
P90-6S	2770 (109.1)	1120 (44.1)	1525 (60.0)	899 (35.4)	1653 (3644)	250 (66.0)

\*Clearance required on both sides of set. Weight with lube oil and coolant, no fuel.